

## SOLUTIONS TO CONCEPTS CHAPTER – 1

1. a) Linear momentum :  $mv = [MLT^{-1}]$   
 b) Frequency :  $\frac{1}{T} = [M^0L^0T^{-1}]$   
 c) Pressure :  $\frac{\text{Force}}{\text{Area}} = \frac{[MLT^{-2}]}{[L^2]} = [ML^{-1}T^{-2}]$
2. a) Angular speed  $\omega = \theta/t = [M^0L^0T^{-1}]$   
 b) Angular acceleration  $\alpha = \frac{\omega}{t} = \frac{M^0L^0T^{-2}}{T} = [M^0L^0T^{-2}]$   
 c) Torque  $\tau = F r = [MLT^{-2}][L] = [ML^2T^{-2}]$   
 d) Moment of inertia  $= Mr^2 = [M][L^2] = [ML^2T^0]$
3. a) Electric field  $E = F/q = \frac{MLT^{-2}}{[IT]} = [MLT^{-3}I^{-1}]$   
 b) Magnetic field  $B = \frac{F}{qv} = \frac{MLT^{-2}}{[IT][LT^{-1}]} = [MT^{-2}I^{-1}]$   
 c) Magnetic permeability  $\mu_0 = \frac{B \times 2\pi a}{I} = \frac{MT^{-2}I^{-1} \times [L]}{[I]} = [MLT^{-2}I^{-2}]$
4. a) Electric dipole moment  $P = ql = [IT] \times [L] = [LTI]$   
 b) Magnetic dipole moment  $M = IA = [I][L^2][L^2I]$
5.  $E = h\nu$  where  $E = \text{energy}$  and  $\nu = \text{frequency}$ .  
 $h = \frac{E}{\nu} = \frac{[ML^2T^{-2}]}{[T^{-1}]} = [ML^2T^{-1}]$
6. a) Specific heat capacity  $= C = \frac{Q}{m\Delta T} = \frac{[ML^2T^{-2}]}{[M][K]} = [L^2T^{-2}K^{-1}]$   
 b) Coefficient of linear expansion  $= \alpha = \frac{L_1 - L_2}{L_0\Delta T} = \frac{[L]}{[L][R]} = [K^{-1}]$   
 c) Gas constant  $= R = \frac{PV}{nT} = \frac{[ML^{-1}T^{-2}][L^3]}{[(\text{mol})][K]} = [ML^2T^{-2}K^{-1}(\text{mol})^{-1}]$
7. Taking force, length and time as fundamental quantity  
 a) Density  $= \frac{m}{V} = \frac{\text{(force/acceleration)}}{\text{Volume}} = \frac{[F/LT^{-2}]}{[L^3]} = \frac{F}{L^4T^{-2}} = [FL^{-4}T^2]$   
 b) Pressure  $= F/A = F/L^2 = [FL^{-2}]$   
 c) Momentum  $= mv$  (Force / acceleration)  $\times$  Velocity  $= [F/LT^{-2}] \times [LT^{-1}] = [FT]$   
 d) Energy  $= \frac{1}{2}mv^2 = \frac{\text{Force}}{\text{acceleration}} \times (\text{velocity})^2$   
 $= \left[ \frac{F}{LT^{-2}} \right] \times [LT^{-1}]^2 = \left[ \frac{F}{LT^{-2}} \right] \times [L^2T^{-2}] = [FL]$
8.  $g = 10 \frac{\text{metre}}{\text{sec}^2} = 36 \times 10^5 \text{ cm/min}^2$
9. The average speed of a snail is 0.02 mile/hr  
 Converting to S.I. units,  $\frac{0.02 \times 1.6 \times 1000}{3600} \text{ m/sec}$  [1 mile = 1.6 km = 1600 m]  $= 0.0089 \text{ ms}^{-1}$   
 The average speed of leopard = 70 miles/hr  
 In SI units  $= 70 \text{ miles/hour} = \frac{70 \times 1.6 \times 1000}{3600} = 31 \text{ m/s}$

10. Height  $h = 75 \text{ cm}$ , Density of mercury  $= 13600 \text{ kg/m}^3$ ,  $g = 9.8 \text{ ms}^{-2}$  then  
 Pressure  $= hfg = 10 \times 10^4 \text{ N/m}^2$  (approximately)  
 In C.G.S. Units,  $P = 10 \times 10^5 \text{ dyne/cm}^2$
11. In S.I. unit  $100 \text{ watt} = 100 \text{ Joule/sec}$   
 In C.G.S. Unit  $= 10^9 \text{ erg/sec}$
12.  $1 \text{ micro century} = 10^4 \times 100 \text{ years} = 10^{-4} \times 365 \times 24 \times 60 \text{ min}$   
 So,  $100 \text{ min} = 10^5 / 52560 = 1.9 \text{ microcentury}$
13. Surface tension of water  $= 72 \text{ dyne/cm}$   
 In S.I. Unit,  $72 \text{ dyne/cm} = 0.072 \text{ N/m}$
14.  $K = kI^a \omega^b$  where  $k = \text{Kinetic energy of rotating body}$  and  $k = \text{dimensionless constant}$   
 Dimensions of left side are,  
 $K = [ML^2T^{-2}]$   
 Dimensions of right side are,  
 $I^a = [ML^2]^a$ ,  $\omega^b = [T^{-1}]^b$   
 According to principle of homogeneity of dimension,  
 $[ML^2T^{-2}] = [ML^2T^{-2}] [T^{-1}]^b$   
 Equating the dimension of both sides,  
 $2 = 2a$  and  $-2 = -b \Rightarrow a = 1$  and  $b = 2$
15. Let energy  $E \propto M^a C^b$  where  $M = \text{Mass}$ ,  $C = \text{speed of light}$   
 $\Rightarrow E = KM^a C^b$  ( $K = \text{proportionality constant}$ )  
 Dimension of left side  
 $E = [ML^2T^{-2}]$   
 Dimension of right side  
 $M^a = [M]^a$ ,  $[C]^b = [LT^{-1}]^b$   
 $\therefore [ML^2T^{-2}] = [M]^a [LT^{-1}]^b$   
 $\Rightarrow a = 1$ ;  $b = 2$   
 So, the relation is  $E = KMC^2$
16. Dimensional formulae of  $R = [ML^2T^{-3}I^{-2}]$   
 Dimensional formulae of  $V = [ML^2T^3I^{-1}]$   
 Dimensional formulae of  $I = [I]$   
 $\therefore [ML^2T^3I^{-1}] = [ML^2T^{-3}I^{-2}] [I]$   
 $\Rightarrow V = IR$
17. Frequency  $f = KL^a F^b M^c$   $M = \text{Mass/unit length}$ ,  $L = \text{length}$ ,  $F = \text{tension (force)}$   
 Dimension of  $f = [T^{-1}]$   
 Dimension of right side,  
 $L^a = [L]^a$ ,  $F^b = [MLT^{-2}]^b$ ,  $M^c = [ML^{-1}]^c$   
 $\therefore [T^{-1}] = K[L]^a [MLT^{-2}]^b [ML^{-1}]^c$   
 $M^0 L^0 T^{-1} = KM^{b+c} L^{a+b-c} T^{-2b}$   
 Equating the dimensions of both sides,  
 $\therefore b + c = 0 \quad \dots(1)$   
 $-c + a + b = 0 \quad \dots(2)$   
 $-2b = -1 \quad \dots(3)$   
 Solving the equations we get,  
 $a = -1$ ,  $b = 1/2$  and  $c = -1/2$   
 $\therefore$  So, frequency  $f = KL^{-1} F^{1/2} M^{-1/2} = \frac{K}{L} F^{1/2} M^{-1/2} = \frac{K}{L} = \sqrt{\frac{F}{M}}$

$$18. a) h = \frac{2S \cos \theta}{\rho g}$$

$$\text{LHS} = [L]$$

$$\text{Surface tension} = S = F/l = \frac{MLT^{-2}}{L} = [MT^{-2}]$$

$$\text{Density} = \rho = M/V = [ML^{-3}T^0]$$

$$\text{Radius} = r = [L], g = [LT^{-2}]$$

$$\text{RHS} = \frac{2S \cos \theta}{\rho g} = \frac{[MT^{-2}]}{[ML^{-3}T^0][L][LT^{-2}]} = [M^0L^1T^0] = [L]$$

$$\text{LHS} = \text{RHS}$$

So, the relation is correct

$$b) v = \sqrt{\frac{p}{\rho}} \text{ where } v = \text{velocity}$$

$$\text{LHS} = \text{Dimension of } v = [LT^{-1}]$$

$$\text{Dimension of } p = F/A = [ML^{-1}T^{-2}]$$

$$\text{Dimension of } \rho = m/V = [ML^{-3}]$$

$$\text{RHS} = \sqrt{\frac{p}{\rho}} = \sqrt{\frac{[ML^{-1}T^{-2}]}{[ML^{-3}]}} = [L^2T^{-2}]^{1/2} = [LT^{-1}]$$

So, the relation is correct.

$$c) V = (\pi r^4 t) / (8 \eta l)$$

$$\text{LHS} = \text{Dimension of } V = [L^3]$$

$$\text{Dimension of } p = [ML^{-1}T^{-2}], r^4 = [L^4], t = [T]$$

$$\text{Coefficient of viscosity} = [ML^{-1}T^{-1}]$$

$$\text{RHS} = \frac{\pi r^4 t}{8 \eta l} = \frac{[ML^{-1}T^{-2}][L^4][T]}{[ML^{-1}T^{-1}][L]}$$

So, the relation is correct.

$$d) v = \frac{1}{2\pi} \sqrt{(mgl/l)}$$

$$\text{LHS} = \text{dimension of } v = [T^{-1}]$$

$$\text{RHS} = \sqrt{(mgl/l)} = \sqrt{\frac{[M][LT^{-2}][L]}{[ML^2]}} = [T^{-1}]$$

$$\text{LHS} = \text{RHS}$$

So, the relation is correct.

$$19. \text{ Dimension of the left side} = \int \frac{dx}{\sqrt{(a^2 - x^2)}} = \int \frac{L}{\sqrt{(L^2 - L^2)}} = [L^0]$$

$$\text{Dimension of the right side} = \frac{1}{a} \sin^{-1}\left(\frac{a}{x}\right) = [L^{-1}]$$

$$\text{So, the dimension of } \int \frac{dx}{\sqrt{(a^2 - x^2)}} \neq \frac{1}{a} \sin^{-1}\left(\frac{a}{x}\right)$$

So, the equation is dimensionally incorrect.

## 20. Important Dimensions and Units :

Physical quantity	Dimension	SI unit
Force (F)	$[M^1L^1T^{-2}]$	newton
Work (W)	$[M^1L^2T^{-2}]$	joule
Power (P)	$[M^1L^2T^{-3}]$	watt
Gravitational constant (G)	$[M^{-1}L^3T^{-2}]$	$N\cdot m^2/kg^2$
Angular velocity ( $\omega$ )	$[T^{-1}]$	radian/s
Angular momentum (L)	$[M^1L^2T^{-1}]$	$kg\cdot m^2/s$
Moment of inertia (I)	$[M^1L^2]$	$kg\cdot m^2$
Torque ( $\tau$ )	$[M^1L^2T^{-2}]$	N-m
Young's modulus (Y)	$[M^1L^{-1}T^{-2}]$	$N/m^2$
Surface Tension (S)	$[M^1T^{-2}]$	N/m
Coefficient of viscosity ( $\eta$ )	$[M^1L^{-1}T^{-1}]$	$N\cdot s/m^2$
Pressure (p)	$[M^1L^{-1}T^{-2}]$	$N/m^2$ (Pascal)
Intensity of wave (I)	$[M^1T^{-3}]$	$watt/m^2$
Specific heat capacity (c)	$[L^2T^{-2}K^{-1}]$	J/kg-K
Stefan's constant ( $\sigma$ )	$[M^1T^{-3}K^{-4}]$	$watt/m^2\cdot k^4$
Thermal conductivity (k)	$[M^1L^1T^{-3}K^{-1}]$	$watt/m\cdot K$
Current density (j)	$[I^1L^{-2}]$	$ampere/m^2$
Electrical conductivity ( $\sigma$ )	$[I^2T^3M^{-1}L^{-3}]$	$\Omega^{-1} m^{-1}$
Electric dipole moment (p)	$[L^1I^1T^1]$	C-m
Electric field (E)	$[M^1L^1I^{-1}T^{-3}]$	V/m
Electrical potential (V)	$[M^1L^2I^{-1}T^{-3}]$	volt
Electric flux ( $\Psi$ )	$[M^1T^3I^{-1}L^{-3}]$	volt/m
Capacitance (C)	$[I^2T^4M^{-1}L^{-2}]$	farad (F)
Permittivity ( $\epsilon$ )	$[I^2T^4M^{-1}L^{-3}]$	$C^2/N\cdot m^2$
Permeability ( $\mu$ )	$[M^1L^1I^{-2}T^{-3}]$	$Newton/A^2$
Magnetic dipole moment (M)	$[I^1L^2]$	N-m/T
Magnetic flux ( $\phi$ )	$[M^1L^2I^{-1}T^{-2}]$	Weber (Wb)
Magnetic field (B)	$[M^1I^{-1}T^{-2}]$	tesla
Inductance (L)	$[M^1L^2I^{-2}T^{-2}]$	henry
Resistance (R)	$[M^1L^2I^{-2}T^{-3}]$	ohm ( $\Omega$ )

\* \* \* \*